

				• ~-	-
		heet	. ^		•
Da.	Lab	11-1-1			

+ 2 hours at + 2 Knots Usage time

Optimized speed of movement 2 Knots

Peak speed 2.5 Knots (in closed-circuit rebreather without load)

Usage time 2.5 Knots More than 1h45 (valited during diving)

Weight in air, in usage configuration 22 Kg

Weight in water 6 kg (adjustable)

50 meters Maximum operating depth

Respiratory device position Chest-mounted or Back-mounted – Oxy – Blending - Air



The composition of the STS kit

Storage and transport	Foam-lined case, compartmentalized

1 interchangeable motorization (motor + propeller + nozzle)

1 pack lithium-ion energy and control equipped with:

- 4 LED indicators showing the battery levels

- 1 power control lever

- 1 emergency stop and shutdown button

Ruggedized connectors for intensive use

1 interchangeable motorization (motor + propeller + nozzle) 1 left thruster

1 pack lithium-ion energy

Ruggedized connectors for intensive use

2 connectors etiro wire connections. 1 battery pack interconnection cable

fits ein the belt

1 clip suspender,

1 belt kit and harness 2 belts (S/M et L/XL), 1 buoyancy belt, 2thight straps, 2 belt/thruster interfaces

2 chargers 1 for each energie pack

1 ou 2 dischargers Option

1 right thruster

1 data reader Option

1 maintenance kit (NTI1) 2 propellers, 1 nozzle, 1 seal kit, 1 tool kit

1user manual on USB key French / English

1 maintenance guide Parts list and refence numbers

Color Black Mat

1 year, parts and labor, direct with Extrem' Vision warranty

EXTREM' VISION